## EUROPEAN PATENT OFFICE

## Patent Abstracts of Japan

PUBLICATION NUMBER

2001098144

**PUBLICATION DATE** 

10-04-01

APPLICATION DATE

29-09-99

APPLICATION NUMBER

11277451

APPLICANT: TOSHIBA CORP;

INVENTOR:

MATSUMOTO KAZUTAKA;

INT.CL.

C08L 63/00 C08K 3/00 C08K 3/02 C08K 3/10 C08K 3/22 C08K 3/40 C08K 5/16

C08K 5/3477 C08K 5/521 C08K 5/5399

TITLE

EPOXY RESIN COMPOSITION AND RESIN-SEALED TYPE SEMICONDUCTOR

**DEVICE** 

ABSTRACT :

PROBLEM TO BE SOLVED: To obtain an epoxy resin composition for semiconductor sealing, having excellent flame retardance and reliability of moisture resistance without using a halogen-based flame retardant or an antimony-based flame retardant and to provide a resin-sealed semiconductor device.

SOLUTION: This resin composition comprises (A) an epoxy resin, (B) a curing agent, (C) a curing promoter, (D) an inorganic filler, (E) a particle obtained by coating the surface of red phosphorus with at least one kind of aluminum hydroxide and a phenol resin, (F) a nitrogen atom-containing compound, (G) an inorganic compound containing at least one kind of a first group consisting of low-melting glass powder, zinc stannate, zinc hydroxystannate, zinc molybdate and molybdenum trioxide.

COPYRIGHT: (C)2001, JPO